

# PluginTikidocfromcode

New in Tiki27, this wiki plugin extends PluginPluginManager to be generic for all preferences, and tracker field options  
So, it can List wiki plugin, module, preference or tracker field documentation for the site

*Introduced in Tiki 27.*

[Go to the source code](#)

*Preferences required: wikiplugin\_tikidocfromcode*

Parameters	Accepted Values	Description	Default	Since
limit	digits	Number of plugins to show. Can be used either with start or plugin as the starting point. Must be an integer 1 or greater.		27
module	text	Name of a module (e.g., calendar_new), or list separated by  , or range separated by -. Single module can be used with <code>limit</code> parameter.		27
plugin	text	Name of a plugin (e.g., backlinks), or list separated by  , or range separated by -. Single plugin can be used with <code>limit</code> parameter.		27
preference	text	Name of a preference (e.g., bigbluebutton_dynamic_configuration), or list separated by  , or range separated by -. Single preference can be used with <code>limit</code> parameter.		27
prefsexport	text	Default preferences export with columns name, description, location or list more separated by  .	name   description   locations	27
start	digits	Start with this plugin record number (must be an integer 1 or greater).		27
trackerfield	text	Name of a tracker field, or list separated by  , or range separated by -. Single preference can be used with <code>limit</code> parameter.		27
type	text	Type of the object to get tiki doc from (e.g: plugin, module, preference, ...)		27
paramtype	alpha	Only list parameters with this <code>doctype</code> setting. Set to <code>none</code> to show only parameters without a type setting and the body instructions.		27
singletitle	(blank) top table	Set placement of plugin name and description when displaying information for only one plugin	none	27

<code>titletag</code>	<code>alnum</code>	Sets the heading size for the title, e.g., <code>h2</code> .	<code>h3</code>	27
<code>info</code>		Determines what information is shown. Values separated with <code> </code> . Ignored when <code>singletitle</code> is set to <code>top</code> or <code>none</code> .	<code>description   parameters   paraminfo</code>	27
<code>showparamtype</code>	(blank)  y n	Show the parameter <code>doctype</code> value.		27
<code>showtopinfo</code>	(blank)  y n	Show information above the table regarding preferences required and the first version when the plugin became available. Shown by default.		27

Example  
This code:

```
{pluginmanager info="description|parameters|paraminfo" plugin="tikimanager"}
```

*Would produce on this site:*

Embed partial or full Tiki Manager instance management functionality in a wiki page.

*Introduced in Tiki 25.*

[Go to the source code](#)

*Preferences required: feature\_tiki\_manager, wikiplugin\_tikimanager*

Parameters	Accepted Values	Description	Default	Since
<code>hideactions</code>	<code>separator: ,</code>	Comma-separated list of actions hidden from the interface. If none are listed, all actions will be available by default.		25.0
<code>instanceIds</code>	<code>separator: ,</code>	Comma-separated list of instance IDs available to manage. For a full list, use Tiki Manager admin page.		25.0
<code>showactions</code>	<code>separator: ,</code>	Comma-separated list of actions shown in the interface. If none are listed, all actions will be available by default.		25.0

