

Mapfile structure

Comments

Any text after a `#` is a comment. Use comments a lot to document your mapfile.

Objects or Groups

A mapfile is composed of several objects. Each object start by the keyword `object` and finishes by `END`. Inside an object there can be several objects with the object starting by its keyword and finishing by `END`.

A mapfile starts by the keyword `MAP` and finishes by `END`

```
%% MAP
```

```
... some lines...
```

```
END # end of map
```

```
/%%
```

Inside the mapfile there are objects like layers, each layer start by the keyword `LAYER` and finishes by `END`

```
%% MAP
```

```
...
```

```
LAYER
```

```
...
```

```
END # end of layer
```

```
LAYER
```

```
...
```

```
END # end of layer
```

```
END # end of map
```

```
/%%
```

Do not try to figure how many END you need to put in the mapfile but use indentation to clearly identify each object with its keyword, text and END keyword. All objects are nested and with proper indentation, they are clearly visible. Indentation is not required but facilitates understanding a mapfile. Adequate comments help a lot too.

A word on colors

The keyword COLOR, OUTLINECOLOR,.. specify the color in the RGB color space. The first value is the red intensity from 0 (no red) to 255, the second value is the green intensity from 0 (no green) to 255 and the last value is the blue intensity from 0 (no blue) to 255. A *COLOR 0 0 0* indicates black while *COLOR 255 255 255* indicates white. *COLOR 0 255 0* would be pure green. The 3 values are compulsory and must be numbers. To select some correct values, use a color selector like the one inside MS-Paint in accessories. You select the color and the RGB values are indicated.

Mapfile header

The mapfile header is composed of several objects for the representation of the maps on the screen, you have the map itself, the web object to define how the web image is created, the reference or overview, the scalebar, the legend and if the map should be queryable. It is better to use pre-canned header and modify little parameters to conform to a specific map. This is the standard header for a map object

pp

Start of map file

```
MAP
NAME "Efate"
STATUS ON
SIZE 400 400
EXTENT 196900 8027100 245000 8073000
UNITS METERS
TRANSPARENT OFF
SHAPEPATH "/var/www/html/map/"
IMAGETYPE png24
FONTSET "fonts/fontset.txt"

OUTPUTFORMAT
NAME png24
DRIVER "GD/PNG"
MIMETYPE "image/png"
IMAGEMODE RGB
EXTENSION "png"
END
```

Start of web interface definition

WEB

TEMPLATE /var/www/html/map/map.html

IMAGEPATH /var/www/html/map/images/

IMAGEURL /map/images/

LOG /var/www/html/map/maplog

END

Start of reference map

REFERENCE
IMAGE /var/www/html/map/data/efate.png
EXTENT 196900 8027100 245000 8073000
STATUS ON
COLOR -1 -1 -1
OUTLINECOLOR 255 0 0
SIZE 95 95
END

Start of legend

LEGEND
KEYSIZE 18 12
LABEL
TYPE BITMAP
SIZE MEDIUM
COLOR 0 0 89
END
STATUS ON
END

Start of scalebar

SCALEBAR
IMAGECOLOR 255 255 255
LABEL
COLOR 0 0 0
SIZE SMALL
END
SIZE 350 5
COLOR 255 255 255
BACKGROUNDCOLOR 0 0 0
OUTLINECOLOR 0 0 0
UNITS kilometers
INTERVALS 5
STATUS ON
END

Start of query definitions

```
QUERYMAP
STATUS ON
STYLE HILITE
END
/PPP
```

Tip: A quick way to start a mapfile is to take the above and just add a END at the end of it. Point to a real image in the REFERENCE section and change all the paths to reflect your own installation. You will have then a working mapfile with no layers. You can then add a GRID to it and start to make modification to suit what you really want to achieve.

It is important here to have the following paths set correctly in regards to where you installed the mapfiles:

- SHAPEPATH
- IMAGEPATH
- IMAGEURL
- IMAGE

See their definition later in the text

Map object

```
PPP
MAP
NAME "Efate"
#name of the map file
STATUS ON
```


is this map on by default

SIZE 400 400

size in pixel of the image map

EXTENT 196900 8027100 245000 8073000

geographic extents of the map

UNITS METERS

units for the geographic extents

TRANSPARENT OFF

the background is not transparent

SHAPEPATH "/var/www/html/map/"

where the shapefiles are stored on the

server also used for directory reference

IMAGETYPE png24

type of image output, here PNG format in 24bits color

FONTSET "fonts/fontset.txt"

file containing the locations of fonts

/pp

Web

This group defines where to store information on the server and how to provide it to the web browser

```
PP
WEB
TEMPLATE /var/www/html/map/map.html
```

location of the template for results

the line needs to be here, but it is

not used (no file at this location)

IMAGEPATH /var/www/html/map/images/

location where to store maps images

IMAGEURL /map/images/

web path for the maps images

LOG /var/www/html/map/maplog

location of the logfile

END
/pp

Metadata

VIEW

View allows you to create views so you can quickly move to the geographic location, for instance moving from one country to another one.

WEB
METADATA
VIEW1 "American Samoa,181.496593149,-20.0990853659,199.331777248,-8.22408536586"
VIEW2 "Australia,97.5030380511,-48.984521576,168.843774449,-1.48452157598"
VIEW3 "Cook Islands,180.098325105,-27.4401969982,215.768693304,-3.69019699813"

...
END

...
END

Each view needs to be numbered in sequential order. Each field is separated by commas, the first field is the name of the view, the following fields are minx,miny,maxx,maxy of the view.

Cf. [Maps MapView](#) for a detailed description.

Reference

This group defines how the overview should be displayed. You use an image representing the area of interest and you specify the coordinates of the location of the edge of the image. The system will draw on the image a rectangle based on the current view, indicating the boundaries of such view.

pp
REFERENCE
IMAGE /var/www/html/map/data/efate.png

location of the image

EXTENT 196900 8027100 245000 8073000

extent of the image

STATUS ON

the overview is on by default

COLOR -1 -1 -1

transparent background

OUTLINECOLOR 255 0 0

the color of the outline

SIZE 95 95

the size of the image in pixels

END

/pp

The tip to create an image for overview, is to not worry about the image at the begining. Any image will do. When the layers are implemented in the mapfile and the main view sounds pretty enough, then select a default view, click *Redraw* if neccessary to get the minx, maxx, miny, maxy parameters in the URL, (if necessary adjust them manualy). Save the current map as an image onto your local machine, use an image editing software to resize the image to the size you want to use in the overview (here 95x95 pixel). Upload the image using the *maps->layer manager* and update the IMAGE link in the REFERENCE group to point to this new image. Finish by entering the correct EXTENTS that corresponds to the minx,miny,maxx,maxy of the map you used to create the overview.

Legend

The legend is linked to each LAYER by the way each object type is represented (POINT, LINE, POLYGON,...) and its COLOR and OUTLINECOLOR and by the NAME used in the CLASS group. It is important to have a meaningful NAME for each CLASS group in every LAYER group. The NAME of the CLASS can be different from the NAME of the layer as a LAYER can have several CLASSes.

PP
LEGEND
KEYSIZE 18 12

the size of the object representing the

geographical object

LABEL
TYPE BITMAP

Font type for the legend name of each

geographical object

SIZE MEDIUM

font size

COLOR 0 0 89

font color

END
STATUS ON

legend is on by default

END
/PP

Scalebar

It is interesting to display a scalebar to get information on distances.

PP
SCALEBAR
IMAGECOLOR 255 255 255

background color of the image placeholder

LABEL
COLOR 0 0 0

color of the labels indicating the distance

SIZE SMALL

size of the labels

END
SIZE 350 5

sixe in pixels of the scalebar

COLOR 255 255 255

color used in the scalebar

BACKGROUNDCOLOR 0 0 0

background color of the drawn scalebar

OUTLINECOLOR 0 0 0

outline color of the salebar

UNITS kilometers

units to be used

INTERVALS 5

How many intervals in total in the

scalebar

STATUS ON

the scalebar is on by default

END

/pp

Query

This group secify that the map will be queryable and how the selected objects should be represented. Include this group even if you don't have a LAYER that can be queryable. It will certainly come later.

pp

QUERYMAP

STATUS ON

the map is queryable by default

STYLE HILITE

the selected object is highlighed

END
/pp

Layers

Vector layer

Let's start by a very simple layer that we will add more features to it. A layer start by the keyword LAYER and finishes by END. It can include CLASS groups, METATADATA groups. For a vector layer the CLASS is compulsory.

Layer Type

The two main types of GIS vector are ESRI shapefiles of Mapinfo TAB files. ESRI shapefiles are natively supported while the Mapinfo files are supported via the OGR library.

All locations of files must be indicated in relative reference to the path indicated by the keyword SHAPEPATH in the MAP group.

If you have a file in "/var/www/html/map/data/mylayer.shp" and SHAPEPATH indicates "/var/www/html/map/" then your file location must be "data/mylayer.shp". Using this convention allows you to easily locate files when you upload them using *Maps->Layer Management*.

File names are case sensitive and spaces in file names must be absolutely avoided. The extensions used for files in layer must stay with the same case sensitivity. A shapefile is usually made of a shp, idx, dbf files while a Mapinfo layer is made of TAB, ID, MAP, DAT (and sometimes IND) files.

Shapefile

```
##
LAYER
NAME "My Layer"
TYPE LINE
STATUS ON
DATA "data/myshapefile.shp"
CLASS
COLOR 255 0 0
NAME "My layer legend"
END # end of class
END # end of layer
/##
```

In this example we see that the file is located in "data/", it is made of LINE objects that will be displayed with the COLOR red. The layer should be drawn on the map by default (STATUS ON), and it will be indicated as "My Layer" in the layer manager on the map, while being indicated as "My layer legend" in the LEGEND.

Mapinfo TAB

The difference with a shapefile is the use of the OGR library to read the Mapinfo files. The keyword CONNECTIONTYPE OGR must be used and the location of the file is given by the keyword CONNECTION instead of DATA. All the rest stay the same.

```
##
LAYER
NAME "My Layer"
TYPE LINE
STATUS ON
CONNECTIONTYPE OGR
CONNECTION "data/mymapinfofile.TAB"
```

```
CLASS
COLOR 255 0 0
NAME "My layer legend"
END # end of class
END # end of layer
/PPP
```

Query

To make the layer queryable add anywhere inside the LAYER object the following lines:

```
TEMPLATE "query.html"
TOLERANCE 3
TOLERANCEUNITS PIXELS
```

The first parameter is necessary but does not need to point to a real file. It is only used outside of tiki maps. The second parameter specifies the pointing TOLERANCE in TOLERANCEUNITS, here 3 pixels. If you click on the map all the objects from this layer which are at less than 3 pixels from the click on the image will be selected. The map is then redrawn and at the bottom of the page will be the information related from the object. Note: if you create a GIS layer which fields contain HTML tags, like for IMG or A (anchor/link), they will be rendered accordingly. This allows you to create a layer pointing to images stored on Tiki.

Labels

You can use querying to know which fields a GIS layer contains. From these fields you can select on to be used as object labels in the map. For instance you have a GIS layer which contains country names. The name of the country is in the field "NAME". You will use LABELITEM "NAME" to tell the mapserver which field to use for labels. Inside the CLASS object, you would specify how you want the labels to be rendered. For instance in our example the layer would look like this:

```
PPP
LAYER
NAME "Country Names"
TYPE POINT
STATUS ON
METADATA
DOWNLOAD "T"
END
LABELITEM "NAME"
LABELCACHE ON
CONNECTIONTYPE OGR
CONNECTION "data/Country.TAB"
CLASS
SYMBOL 0
COLOR 0 0 0
NAME "Country Names"
LABEL
COLOR 0 0 0
FONT arial
TYPE TRUETYPE
POSITION CC
PARTIALS TRUE
SIZE 7
BUFFER 1
OUTLINECOLOR 255 255 255
END
END
END
```

/pp

In this example LABEL is black (COLOR 0 0 0) using the arial FONT which is a TRUETYPE font. The POSITION of the label is Center/Center in regard to the POINT object. If an object is not fully on the map, the LABEL is still drawn (PARTIAL TRUE). The SIZE of the label is 7 points. There are no labels closer than 1 pixels from each others (BUFFER 1). For this last parameter to work, you need to enable the LABELCACHE. Finally the label is surrounded by a white outline (OUTLINECOLOR 255 255 255).

Thematic Mapping

Each layer contains one or more CLASS. The CLASS defines how each object should be drawn on the screen. by using CLASSITEM, you can use one field to separate objects in classes. For instance all the bathymetric lines which depth is between -100m and -500m belong to one class while each bathymetric lines which depth is between -500m and -1000m belong to another class. The separation into CLASS is made using an EXPRESSION in each CLASS. The EXPRESSION uses simple logic based on the field in CLASSITEM.

For instance in the example below we use the field "value" which contains the water depth of the LINE object to display this line object in various colors depending of the depth. If the EXPRESSION is true then the parameters in the CLASS apply. A CLASS without an EXPRESSION is a default CLASS for all the objects which have not been classified otherwise.

pp

LAYER

NAME "Bathymetry 20m"

TYPE LINE

STATUS OFF

METADATA

WIKI "FijiBathymetry"

END

TEMPLATE "query.html"

TOLERANCE 3

TOLERANCEUNITS PIXELS

LABELITEM "Value"

CLASSITEM "Value"

LABELCACHE ON

CONNECTIONTYPE OGR

CONNECTION "data/fiji/viti_bathy_contour.TAB"

CLASS

SYMBOL 0

COLOR 0 200 255

NAME "Bathymetry 2.5m >-50m"

expression ([Value](#)>-50)

LABEL

ANGLE AUTO

COLOR 0 0 0

FONT arial

TYPE TRUETYPE

POSITION cc

PARTIALS FALSE

BUFFER 5

SIZE 6

OUTLINECOLOR 200 200 200

END

END

CLASS

SYMBOL 0

COLOR 0 100 255

NAME "Bathymetry 20m >-500m"

expression ([Value](#)<-50 AND [Value](#)>=-500)

LABEL

ANGLE AUTO

FONT arial

COLOR 0 0 0

TYPE TRUETYPE

POSITION cc

PARTIALS FALSE

```
BUFFER 5
SIZE 6
OUTLINECOLOR 200 200 200
END
END
END
/PP
```

Metadata

Inside a LAYER group you can have a METADATA group. Some of this metadata is used for special purposes inside tikiwiki. There is only one METADATA group inside a LAYER group.

WIKI

Using WIKI creates a link from the layer name to a wiki page. Use the wiki page to indicate some information on the layer:

- custodian
- ownership
- date of creation
- accuracy
- history
- datum/projection
- interesting layer features
- ...

```
PP
METADATA
WIKI "MyLayerPage"
END
/PP
```

DOWNLOAD

If DOWNLOAD is set to "T" then the files that forms the layer can be downloaded by a registered user.

```
PP
METADATA
DOWNLOAD "T"
END
/PP
```

The system selects all the files with the same base name as defined in the LAYER DATA or CONNECTION clause but with different extension. However if one of these files has the extension NDL, the download is disabled. This allows to upload GIS data that can only be viewable.

Raster layer

The easiest way to handle raster layers is to use Geotiff images which contain projection information. However making geotiff images may need advanced remote sensing software. The other way is to use an additional file which contains information about the coordinates of the pixels in the image file.

When several images are used instead of using a layer for each image they can be tiled. A shapefile is created with a rectangle for each image which helps the system to find the right image for the right location.

Geotiff

Using a geotiff image in a layer is simple, the TYPE RASTER is used with DATA pointing to the tiff file. the keyword OFFSITE is used to define which color in the tiff image should be used for transparency. This is useful when tiling or overlapping several images.

```
%%  
LAYER  
NAME "DTM 50m"  
TYPE RASTER  
STATUS OFF  
DATA "data/fiji/VLevudtm.tif"  
OFFSITE 0 0 0  
END  
/%%
```

Image Tiles

Image tiles are created using utility tools from the mapserver software. The utility is called gdaltindex and parses mainly geotiff images to get their boundaries and create a shapefile containing an outline for each of the images. Under Maps->Layer Management, at the bottom of the page a utility is available to generate the shapefile. Basically upload the images to the right directory. The images should have the same name prefix. Then reference all these images with a wildcard and name the shapefile to be created. For instance you can upload coralcoastsigatoka.tif, coralcoastmomi.tif, coralcoastnavua.tif and reference them as coralcoast*.tif and create the shapefile img_index.shp

```
%%  
LAYER  
NAME "Coral Coast 4m IKONOS"  
TYPE RASTER  
METADATA  
WIKI "FijiImagery"  
END  
STATUS ON  
TILEINDEX "data/fiji/img_index.shp"  
TILEITEM "Location"  
OFFSITE 0 0 0  
END  
/%%
```

Grid Layer

A grid layer allows you to draw a grid in the local coordinates on your map. It is useful to find location of objects on the map. For best effect the grid must be the last layer in the mapfile to be drawn the last.

```
%%  
LAYER  
NAME "Grid"  
TYPE LINE  
STATUS OFF  
CLASS  
COLOR 0 0 0  
LABEL  
FONT arial # must be in your FONTSET  
TYPE TRUETYPE  
SIZE 8  
COLOR 0 0 0  
OUTLINECOLOR 255 255 255  
END  
END  
GRID  
MINARCS 2  
MAXARCS 6  
END  
END  
/%%
```