

PluginTikidocfromcode

New in Tiki27, this [wiki plugin](#) extends [PluginPluginManager](#) to be generic for all preferences, and tracker field options.

So, it can List wiki plugin, module, preference or tracker field documentation for the site

Introduced in Tiki 27.

[Go to the source code](#)

Preferences required: `wikiplugin_tikidocfromcode`

Parameters	Accepted Values	Description	Default	Since
<code>limit</code>	digits	Number of plugins to show. Can be used either with start or plugin as the starting point. Must be an integer 1 or greater.		27
<code>module</code>	text	Name of a module (e.g., calendar_new), or list separated by , or range separated by -. Single module can be used with <code>limit</code> parameter.		27
<code>plugin</code>	text	Name of a plugin (e.g., backlinks), or list separated by , or range separated by -. Single plugin can be used with <code>limit</code> parameter.		27
<code>preference</code>	text	Name of a preference (e.g., bigbluebutton_dynamic_configuration), or list separated by , or range separated by -. Single preference can be used with <code>limit</code> parameter.		27
<code>prefsexport</code>	text	Default preferences export with columns name, description, location or list more separated by .	name description locations	27
<code>start</code>	digits	Start with this plugin record number (must be an integer 1 or greater).		27
<code>trackerfield</code>	text	Name of a tracker field, or list separated by , or range separated by -. Single preference can be used with <code>limit</code> parameter.		27
<code>type</code>	text	Type of the object to get tiki doc from (e.g: plugin, module, preference, ...)		27
<code>paramtype</code>	alpha	Only list parameters with this doctype setting. Set to none to show only parameters without a type setting and the body instructions.		27
<code>singletitle</code>	(blank) top table	Set placement of plugin name and description when displaying information for only one plugin	none	27
<code>titletag</code>	alnum	Sets the heading size for the title, e.g., h2.	h3	27
<code>info</code>		Determines what information is shown. Values separated with . Ignored when <code>singletitle</code> is set to top or none.	description parameters paraminfo	27

showparamtype	(blank) y n	Show the parameter doctype value.	27
showtopinfo	(blank) y n	Show information above the table regarding preferences required and the first version when the plugin became available. Shown by default.	27

Example

This code:

```
{pluginmanager info="description|parameters|paraminfo" plugin="tikimanager"}
```

Would produce on this site:

Embed partial or full Tiki Manager instance management functionality in a wiki page.

Introduced in Tiki 25.

[Go to the source code](#)

Preferences required: feature_tiki_manager, wikiplugin_tikimanager

Parameters	Accepted Values	Description	Default	Since
hideactions	<i>separator: ,</i>	Comma-separated list of actions hidden from the interface. If none are listed, all actions will be available by default.		25.0
instanceIds	<i>separator: ,</i>	Comma-separated list of instance IDs available to manage. For a full list, use Tiki Manager admin page.		25.0
showactions	<i>separator: ,</i>	Comma-separated list of actions shown in the interface. If none are listed, all actions will be available by default.		25.0