

Changing the web server configuration

Generally, you shouldn't need to change your [httpd.conf](#), but if you do, this page is to share tips & tricks about Tiki-related configs.

Note also that some hosting services do not allow you to change the httpd.conf file, because it may be shared between different accounts running on the same web server. In those cases, some of the configurations suggested below can still be done by putting them in the .htaccess file.

Exploiting caches for static resource files

There are many files on your site that never change. Things like image files for icons and logos, CSS files for styles, javascript, etc. Yet, if your web server is not configured properly, each request made by a user will redownload them everytime, without looking in any cache.

On some slow servers (or heavily shared server farms like BlueHost), this can add several seconds to the loading time of every page. To avoid this, you must set an expiry date on files which are of a static type. On this type of server, this technique has been known to shave off a couple of seconds from the loading time of pages.

For example:

```
ExpiresActive On # dont cache html as people wont get page updates: # ExpiresByType text/html "access plus 1 month"
ExpiresByType text/css "access plus 6 month" ExpiresByType text/javascript "access plus 6 month" ExpiresByType
image/gif "access plus 6 month" ExpiresByType image/jpeg "access plus 6 month" ExpiresByType image/png "access plus 6
month" Header append Cache-Control "public"
```

Dealing with scripts that take too long to run

```
# time out connections earlier, 300 is too much Timeout 150 # clients may keep alive existing connections KeepAlive On
MaxKeepAliveRequests 120 KeepAliveTimeout 15 !Starting more than one children # switch off hostname lookups, that
needs some time HostnameLookups Off MinSpareServers 6 MaxSpareServers 8 StartServers 10 # 10 clients should be
enough, but for peaks 50 might be good. # depends on your memory, 50 works for 2GB memory MaxClients 50 # dont set
this to a value too low: MaxRequestsPerChild 1500
```

Virtual Host Settings

Limit connections from one ip to a given number.

Homepage of mod_limitipconn

- [mod_limitipconn.c page](#)

Customlog /var/log/nameofvirtualhost-access-denied.log combined env=LIMITIP MaxConnPerIP 10 NoIPLimit img/*